

THE REC-THY PACKAGE

PETER M. GERDES (GERDES@INVARIANT.ORG)

2025/04/19: Version 4.5

ABSTRACT. The rec-thy package is designed to help mathematicians publishing papers in the area of recursion theory (aka Computability Theory) easily use standard notation. This includes easy commands to denote Turing reductions, Turing functionals, r.e. sets, stagewise computations, forcing and syntactic classes.

1. INTRODUCTION

This package aims to provide a useful set of L^AT_EX macros covering basic computability theory notation. Given the variation in usage in several areas this package had to pick particular notational conventions. The package author would like to encourage uniformity in these conventions but has included a multitude of package options to allow individual authors to choose alternative conventions or exclude that part of the package. Some effort has been made to align the semantic content of documents created with this package with the L^AT_EX source. The author hopes that eventually this package may be incorporated into some larger package for typesetting papers in mathematical logic.

While computability theory is now the more popular name for the subject also known as recursion theory the author deliberately choose to title this package rec-thy to avoid confusion with the proliferation of packages for typesetting computer science related disciplines. While the subject matter of computability theory and theoretical computer science overlap significantly the notational conventions often differ.

Comments, patches, suggestions etc.. are all welcome. This project is hosted on github at <https://github.com/TruePath/Recursion-Theory-Latex-Package>.

2. USAGE

Include the package in your document by placing `\usepackage{rec-thy}` into your preamble after placing `rec-thy.sty` somewhere T_EX can find it. The commands in this package have been divided into related groups. The commands in a given section can be disabled by passing the appropriate

package option. For instance to disable the commands in the general mathematics section and the delimiters section you would include the following in your preamble `\usepackage[nomath,nodelim]{rec-thy}`.

2.1. Versioning. Over time the package may evolve in incompatible ways to improve usability. To guarantee that your documents continue to produce the same output **always** include a package option setting the version, e.g., `\usepackage[version4.0]{rec-thy}`. You can always find the version of the package you are using by either looking in your log files during compilation or opening up this documentation and seeing the version number displayed.

2.2. Alternate Symbols. While the symbols used by default in the package are suggested for adoption to achieve greater consistency users may wish to specify their own symbols. The following package options enable such changes.

`modulescr` Sets the script used to typeset the `\module` command. Default is `mathcal`.

`reqscr` Sets the script used to typeset requirements. Default is `mathscr`.

`pfcasefont` Sets the script used to typeset Case in the cases helper.

`emptystr` Sets the empty string symbol. Default is `\langle \rangle`

`concatsym` Sets the concat symbol. Default is `\wedge`

`recfnlsym` Sets the symbol used for recursive functionals. Default is `\Phi`.

`recfsym` Sets the symbol used for recursive functions. Default is `\phi`.

`usesym` Sets the symbol used for the use operator. Default is `\mathfrak{u}` where this is printed using `\symbolfrak` if `unicode-math` is loaded and with `\mathfrak{u}` otherwise.

`lstrdelim,rstrdelim` Left and right delimiters for `\str`

`lcodedelim,rcodedelim` Left and right delimiters for `\code`

`lpairdelim,rpairlim,pairsup` Left and right delimiters for `\pair` and superscript.

`midincompat` No argument is taken. Chooses to use the vertical bar for the incompatibility symbol.

3. COMMANDS

A few general conventions are usually followed in the commands. Whenever an operator can be used as a binary operator (as in $X \cup Y$) and as an operation on some collection $\bigcup_{i \in \omega} X_i$ the binary operator will begin with a lowercase letter `\union` and the operation on the collection will begin with

a capital letter \Union. If the first letter is already capitalized then the second letter is used instead.

Objects that have a natural stagewise approximation generally admit an optional argument in brackets to specify a stage. For instance \REset[s]{e} yields $W_{e,s}$. An optional argument in parenthesis is used for relativization. For instance \REset(X){e} produces W_e^X . For the formula classes square brackets are used to indicate an oracle to be placed in the superscript, e.g., \pizn[X]{2} yields $\Pi_2^{0,X}$ while parenthesis place the value in parentheses after the symbol as in $\Pi_2^0(X)$. To give boldcase versions of formulas classes a star should be used immediately following the command as in $\mathbf{\Pi}_2^0(X)$. Users of the package should take care to wrap arguments that may themselves include brackets or parenthesis in braces. For example \REset(\REset(X){e}){i} should be fixed to \REset(\{\REset(X){e}\}){i}.

Unless indicated otherwise all macros are to be used inside math mode.

3.1. Priority Trees. Note the commands in this section double as suggestions for standardized notation.

\PriorityTree	T	Priority Tree
\tpath	f	Truepath.
\tpath[s]	f _s	Approximate Truepath.
\xi \lefttof \eta	ξ < _L η	The left of relation for priority tree arguments
\module[R][X]{i,j}	R _{i,j} ^X	Module in tree construction (superscript optional arg)

3.2. Computations. To disable these commands pass the option `nocomputations`.

To specify an alternative symbol for either recursive functionals or recursive functions pass `recfnlsym=macroname` or `recfsym=macroname`. For instance, to use ψ for recursive functions and Ψ for recursive functionals pass the options `recfsym=psi`, `recfnlsym=Psi`.

\murec{x}{f(x)>1}	μx (f(x) > 1)	Least x satisfying condition.
\recf{e}	φ _e	
\recf[s]{e}	φ _{e,s}	Computable functions
\recf{e}(x)	φ _e (x)	
\recf[s]{e}(x)	φ _{e,s} (x)	
\recf(Y){e}	φ _e ^Y	
\recf[s](Y){e}	φ _{e,s} ^Y	

$\backslash \text{recf}(Y)\{e\}(x)$	$\phi_e^Y(x)$	
$\backslash \text{recf}[s](Y)\{e\}(x)$	$\phi_{e,s}^Y(x)$	
$\backslash \text{recfnl}\{e\}\{Y\}\{x\}$	$\Phi_e(Y; x)$	
$\backslash \text{recfnl}[s]\{e\}\{Y\}\{x\}$	$\Phi_{e,s}(Y; x)$	Computable functionals
$\backslash \text{recfnl}\{e\}\{Y\}\{\}$	$\Phi_e(Y)$	
$\backslash \text{recfnl}\{e\}\{\}\{x\}$	$\Phi_e(x)$	
$\backslash \text{recfnl}\{e\}\{\}\{\}$	Φ_e	
$\backslash \text{recfnl}\{e\}\{\}\{\} \backslash \text{cequiv} \backslash \text{recfnl}\{i\}\{\}\{\}$	$\Phi_e \simeq \Phi_i$	Equivalent computations
$\backslash \text{recfnl}\{e\}\{\}\{\} \backslash \text{ncequiv} \backslash \text{recfnl}\{i\}\{\}\{\}$	$\Phi_e \not\simeq \Phi_i$	Inequivalent computations
$\backslash \text{recfnl}\{e\}\{\}\{x\} \backslash \text{conv}$	$\Phi_e(x) \downarrow$	Convergence
$\backslash \text{recfnl}\{e\}\{\}\{x\} \backslash \text{conv}[s]$	$\Phi_e(x) \downarrow_s$	
$\backslash \text{recfnl}\{e\}\{\}\{x\} \backslash \text{nconv}$	$\Phi_e(x) \ddagger$	Divergence
$\backslash \text{recfnl}\{e\}\{\}\{x\} \backslash \text{nconv}[s]$	$\Phi_e(x) \ddagger_s$	
$\backslash \text{use}\{\backslash \text{recfnl}\{e\}\{Y\}\{x\}\}$	$u[\Phi_e(Y; x)]$	Use of a computation.
$\backslash \text{REset}\{e\}$	W_e	
$\backslash \text{REset}[s]\{e\}$	$W_{e,s}$	c.e. sets
$\backslash \text{REset}(X)\{e\}$	W_e^X	
$\backslash \text{REset}[s](X)\{e\}$	$W_{e,s}^X$	
$\backslash \text{Hop}\{e\}(X)$	$\mathcal{H}_e(X)$	
$\backslash \text{Hop}[s](X)\{e\}$	$\mathcal{H}_{e,s}(X)$	Hop sets
$\backslash \text{Hop}[s]\{e\}$	$\mathcal{H}_{e,s}(\emptyset)$	
$\backslash \text{Hop}\{e\}$	$\mathcal{H}_e(\emptyset)$	
$\backslash \text{REAop}\{e\}\{\alpha\}$	\mathcal{J}_e^α	

3.3. **Degrees.** To disable these commands pass the option `nodegrees`.

$\backslash \text{Tdegrees}$	\mathcal{D}	The structure of $\mathcal{P}(\omega)$ under \leq_T
$\backslash \text{strcD}$		alternate command
$\backslash \text{REdegrees}$	\mathcal{R}	The structure of r.e sets under \leq_T
$\backslash \text{strcR}$		alternate command
$\backslash \text{Adegrees}$	\mathcal{D}_a	The structure of $\mathcal{P}(\omega)$ under \leq_a

$\backslash\text{strcDa}$		alternate command
$\backslash\text{AREAdegrees}$ $\backslash\text{strcRa}$	FOO	The structure of the ω -REA sets under \leq_a alternate command
$\backslash\text{Tdeg}\{d\}$	d	indicated that the variable/entity is a Turing degree
$\backslash\text{Tjump}\{X\}$ $\backslash\text{jump}\{X\}$	X'	Turing jump
$\backslash\text{jjump}\{X\}$	X''	
$\backslash\text{jumpn}\{X\}\{n\}$	$X^{(n)}$	
$\backslash\text{Tzero}$	0	Computable degree
$\backslash\text{zeroj}$	$0'$	
$\backslash\text{zerojj}$	$0''$	
$\backslash\text{zerojjj}$	$0'''$	
$\backslash\text{zeron}\{n\}$	$0^{(n)}$	
$X \backslash\text{Teq } Y$	$X \equiv_T Y$	Turing equivalence
$X \backslash\text{nTeq } Y$	$X \not\equiv_T Y$	Turing inequivalence
$X \backslash\text{Tlneq } Y$	$X \not\leq_T Y$	
$X \backslash\text{Tleq } Y$	$X \leq_T Y$	
$X \backslash\text{Tgneq } Y$	$X \not\geq_T Y$	
$X \backslash\text{Tgeq } Y$	$X \geq_T Y$	
$X \backslash\text{Tgtr } Y$	$X >_T Y$	
$X \backslash\text{Tless } Y$	$X <_T Y$	
$X \backslash\text{ntleq } Y$	$X \not\leq_T Y$	
$X \backslash\text{ntgeq } Y$	$X \not\geq_T Y$	
$X \backslash\text{Tincompat } Y$	$X \perp_T Y$	Turing incompatibility
$X \backslash\text{Tcompat } Y$	$X \asymp_T Y$	Turing compatibility
$\backslash\text{Tdeg}\{d\} \backslash\text{join } \backslash\text{Tdeg}\{d'\}$ $\backslash\text{Join}_{\{i\}} \backslash\text{in } \backslash\text{omega} \} \backslash\text{Tdeg}\{d_i\}$	$d \vee d'$ $\bigvee_{i \in \omega} d_i$	Join of degrees
$\backslash\text{Tdeg}\{d\} \backslash\text{meet } \backslash\text{Tdeg}\{d'\}$ $\backslash\text{Meet}_{\{i\}} \backslash\text{in } \backslash\text{omega} \} \backslash\text{Tdeg}\{d_i\}$	$d \wedge d'$ $\bigwedge_{i \in \omega} d_i$	Meet of degrees (when defined)
$X \backslash\text{Tplus } Y$	$X \oplus Y$	Effective join of sets (alias for $\backslash\text{oplus}$)
$\backslash\text{TPlus}_{\{i\}} \backslash\text{in } \backslash\text{omega} \} X_i$ $\backslash\text{Oplus}_{\{i\}} \backslash\text{in } \backslash\text{omega} \} X_i$	$\bigoplus_{i \in \omega} X_i$	Effective join of sets alternative name
$X \backslash\text{ttlneq } Y$	$X \not\leq_{tt} Y$	Truth table reducibilities
$X \backslash\text{ttleq } Y$	$X \leq_{tt} Y$	
$X \backslash\text{ttgneq } Y$	$X \not\geq_{tt} Y$	
$X \backslash\text{ttgeq } Y$	$X \geq_{tt} Y$	

$X \setminus \text{ttgtr } Y$	$ X >_{\text{tt}} Y $	
$X \setminus \text{ttless } Y$	$ X <_{\text{tt}} Y $	
$X \setminus \text{ttnleq } Y$	$ X \not\leq_{\text{tt}} Y $	
$X \setminus \text{ttngeq } Y$	$ X \not\geq_{\text{tt}} Y $	
$\setminus \text{Azero}$	$ \mathbf{0}_a $	Arithmetic degree
$\setminus \text{Azeroj}$	$ \mathbf{0}_a' $	
$\setminus \text{Azerojj}$	$ \mathbf{0}_a'' $	
$\setminus \text{Azerojjj}$	$ \mathbf{0}_a''' $	
$\setminus \text{Azeron}\{n\}$	$ \mathbf{0}_a^{(n)} $	
$X \setminus \text{Aeq } Y$	$ X \equiv_a Y $	Arithmetic equivalence
$X \setminus \text{nAeq } Y$	$ X \not\equiv_a Y $	Arithmetic inequivalence
$X \setminus \text{Alneq } Y$	$ X \leq_a Y $	
$X \setminus \text{Aleq } Y$	$ X \leq_a Y $	
$X \setminus \text{Agneq } Y$	$ X \geq_a Y $	
$X \setminus \text{Ageq } Y$	$ X \geq_a Y $	
$X \setminus \text{Agtr } Y$	$ X >_a Y $	
$X \setminus \text{Aless } Y$	$ X <_a Y $	
$X \setminus \text{nAleq } Y$	$ X \not\leq_a Y $	
$X \setminus \text{nAgeq } Y$	$ X \not\geq_a Y $	
$X \setminus \text{Aincompat } Y$	$ X \perp_a Y $	Turing incompatibility
$X \setminus \text{Acompat } Y$	$ X \asymp_a Y $	Turing compatibility

3.4. Requirement Assistance. To disable these commands pass the option `noreqhelper`. To disable the hyperlinked requirements pass `nohyperreqs`. Math mode is not required for $\text{\req}\{R\}\{e\}$

$\text{\req}\{R\}\{e\}$	\mathcal{R}_e	Requirement
$\text{\req}\{R\}[\text{\nu}]\{e\}$	\mathcal{R}_e^ν	
$\text{\req*}\{R\}\{e\}$	\mathcal{R}_e	Requirement without hyperlinks
$\text{\req*}\{R\}[\text{\nu}]\{e\}$	\mathcal{R}_e^ν	

We also introduce the following environments for introducing requirements. The requirement environment is used as follows

```
\begin{environment}{\req\{R^*\}\{r,j\}}
```

```
\recfnl{r}{B}{} = \Reset{j} \implies
  \exists[k] \left( \Upsilon^j_k(C \oplus W_j) = B \right) \lor
  \Reset{j} \leq_T 0
\end{requirement}
```

Giving output

$$\mathcal{R}_{r,j}^*: \Phi_r(B) = W_j \implies [\exists k] (\Upsilon_k^j(C \oplus W_j) = B) \vee W_j \leq_T 0$$

The require environment merges the `\req{\nu}{R}{e}` command directly into the environment arguments. It also creates an automatic label which makes use of the 1st and 2nd arguments but assumes the third argument contains only indexes whose names are subject to change. Unless `nohyperreqs` is passed the `\req{\nu}{R}{e}` automatically links to the defining require environment.

```
\begin{require}{i}
  \recfnl{i}{B}{} = \Reset{i} \implies \exists[k]
    \left( \Upsilon^i_k(C \oplus W_i) = B \right) \lor
    \Reset{j} \leq_T 0
\end{require}
```

Giving output

$$\mathcal{R}_i: \Phi_i(B) = W_i \implies [\exists k] (\Upsilon_k^i(C \oplus W_i) = B) \vee W_j \leq_T 0$$

To list multiple requirements at once without introducing unnecessary spaces we also introduce the requirements environment which can be used as follows. Note that one may *not* end the final line with a linebreak or an undesired tag will appear.

```
\begin{requirements}
\require{P}[A]{e} A \neq \recfnl{i}{}{} \\
\require{P}[B]{e} B \neq \recfnl{i}{}{} \\
\require{R}{i,\hat{i},j,\hat{j}} \recfnl{i}{A}{} = \hat{A} \land \recfnl{\hat{i}}{\hat{A}}{} = A \land
\recfnl{j}{B}{} = \hat{B} \land \recfnl{\hat{j}}{\hat{B}}{} = B \implies \Gamma(\hat{A} \setminus \text{symdiff} \hat{B}) = A \oplus B
\end{requirements}
```

$$\mathcal{P}_e^A: \quad A \neq \Phi_i$$

$$\mathcal{P}_e^B: \quad B \neq \Phi_i$$

$$\mathcal{R}_{i,\hat{i},j,\hat{j}}: \quad \Phi_i(A) = \hat{A} \wedge \Phi_{\hat{i}}(\hat{A}) = A \wedge \Phi_j(B) = \hat{B} \wedge \Phi_{\hat{j}}(\hat{B}) = B \implies \Gamma(\hat{A} \Delta \hat{B}) = A \oplus B$$

3.5. General Math Commands. To disable these commands pass the option `nomath`.

<code>\eqdef</code>	$\stackrel{\text{def}}{=}$	Definitional equals
<code>\iffdef</code>	$\stackrel{\text{def}}{\iff}$	Definitional equivalence
<code>\aut</code>	Aut	Automorphisms of some structure
<code>\Ord</code>	Ord	Set of ordinals
<code>\abs{x}</code>	$ x $	Absolute value
<code>\dom</code>	dom	Domain
<code>\rng</code>	rng	Range
<code>f\restr{X}</code>	$f\restriction_X$	Restriction
<code>\ordpair{x}{y}</code>	(x, y)	Ordered Pair
<code>f \compproc g</code> <code>f \compose g</code>	$f \circ g$	Function composition
<code>f: X \pmapsto Y</code>	$f : X \rightarrowtail Y$	partial function from X to Y .
<code>f: Y \pmapsfrom X</code>	$f : Y \rightarrowtail X$	partial function from X to Y .
<code>f: X \fpmpto Y</code>	$f : X \rightarrowtail_{<\infty} Y$	finite partial function from X to Y .
<code>f: Y \fpmapsfrom X</code>	$f : Y \rightarrowtail_{<\infty} X$	finite partial function from X to Y .
<code>\ParFuncs{X}{Y}</code>	$Y^{<X}$	set of partial functions from X to Y .
<code>\FinParFuncs{X}{Y}</code>	$Y^{<\infty X}$	set of finite partial functions from X to Y .
<code>\(` \ensuretext{blah} `)</code> <code>\ensuretext{blah}</code>	blah	Types argument in text mode
<code>\quotient{X}{Y}</code>	X / Y	

3.6. Operators. Misc operators used in logic and computability. To disable these commands pass the option `nooperators`.

<code>x \meet y</code>	$x \wedge y$	Meet operation
<code>\Meet_{i\in\omega} x_i</code>	$\bigwedge_{i \in \omega} x_i$	
<code>x \join y</code>	$x \vee y$	Join operation
<code>\Join_{i\in\omega} x_i</code>	$\bigvee_{i \in \omega} x_i$	
<code>x \xor y</code>	$x \text{ xor } y$	
<code>\Land \phi_i</code>	$\bigwedge \phi_i$	Operator form of and
<code>\Lor \phi_i</code>	$\bigvee \phi_i$	Operator form of or
<code>\LLand \phi_i</code>	$\mathbb{A} \phi_i$	Infinitary conjunction
<code>\LLor \phi_i</code>	$\mathbb{V} \phi_i$	Infinitary disjunction

3.7. Set Notation. To disable these commands pass the option `nosets`.

Note that `\Cross` and `\cross` overwrite the existing commands saving them as `\CrossOrig` and `\crossOrig` respectively as these commands have varying meanings between different font packages. However, the other commands avoid overwriting existing commands with that name

$\set{(x,y)}{x > y}$	$\{(x, y) \mid x > y\}$	Set notation
$\set{(x,y)}$	$\{(x, y)\}$	
\card{X}	$ X $	Cardinality
$X \cup Y$	$X \cup Y$	Union
$\bigcup_{i \in \omega} X_i$	$\bigcup_{i \in \omega} X_i$	
$X \cap Y$	$X \cap Y$	Intersection
$\bigcap_{i \in \omega} X_i$	$\bigcap_{i \in \omega} X_i$	
$X \times Y$	$X \times Y$	Cartesian product (Cross Product)
$\prod_{i \in \omega} X_i$	$\prod_{i \in \omega} X_i$	
$\text{powset}\{\omega\}$	$\mathcal{P}(\omega)$	Powerset
$\text{powset}[\alpha]\{\omega\}$	$\mathcal{P}_\alpha(A)$	Subsets of A of size $< \alpha$
eset	\emptyset	Emptyset abbreviation
$x \notin A$	$x \notin A$	not an element
$\text{setcmp}\{X\}$	\overline{X}	Set compliment
$X \text{sympdiff } Y$	$X \Delta Y$	Symmetric difference

3.8. Improved Symbols and MnSymbol Imports. Unless the option `nosymb` is passed a number of symbols are (re)defined for better typesetting. To prevent only redefinition of `\langle` and `\rangle` (e.g. to use the XITS unusual default) pass the option `nodoubleangles`. A couple new symbols which can't be easily created without the MnSymbol font are also defined and are listed below.

\Searrow	\rightsquigarrow	double searrow
\nSearrow	\nrightsquigarrow	negated double searrow

3.9. Quantifiers. To disable these commands pass the option `noquants`. The commands `\exists` and `\forall` are standard but the package extends them.

<code>\exists[x < y]</code>	$[\exists x < y]$	
<code>\exists(x < y)</code>	$(\exists x < y)$	
<code>\exists*</code>	\exists^∞	
<code>\existsinf</code>		
<code>\exists*[x < y]</code>	$[\exists^\infty x < y]$	
<code>\exists*(x < y)</code>	$(\exists^\infty x < y)$	
<code>\nexists[x < y]</code>	$[\nexists x < y]$	
<code>\nexists(x < y)</code>	$(\nexists x < y)$	
<code>\nexists*</code>	\nexists^∞	
<code>\nexistsinf</code>		
<code>\nexists*[x < y]</code>	$[\nexists^\infty x < y]$	
<code>\nexists*(x < y)</code>	$(\nexists^\infty x < y)$	
<code>\forall[x < y]</code>	$[\forall x < y]$	
<code>\forall(x < y)</code>	$(\forall x < y)$	
<code>\forall*</code>	\forall^*	
<code>\forallallae</code>		For almost all.
<code>\forall*[x < y]</code>	$[\forall^* x < y]$	
<code>\forall*(x < y)</code>	$(\forall^* x < y)$	

3.10. **Spaces.** To disable these commands pass the option `nospaces`.

<code>\bstrs</code>	$2^{<\omega}$	Finite binary strings
<code>\cbstrs</code>	$2^{<\omega^{<\omega}}$	Finite sequence of binary strings (regarded as columnise specification)
<code>\wstrs</code>	$\omega^{<\omega}$	Finite sequences of integers
<code>\cantor</code>	2^ω	Cantor space
<code>\baire</code>	ω^ω	Baire space
<code>\Baire</code>	\mathcal{N}	Alternate baire space
<code>\bpfuncs</code>	$\{0, 1, \uparrow\}^{<\omega}$	Finite binary partial functions

3.11. **Strings.** To disable these commands pass the option `nostrings`.

To specify an alternative symbol for the empty string pass `emptystr=macroname`. For instance, to use λ as the empty string pass `emptystr=lambda`. Similarly, to specify an alternate value for the concatenation symbol pass `concatsym=macroname`,

e.g., if you specify `\def\plus{+}` and then pass `concatsym=plus` the concatenation symbol would be changed to `+`.

To use `\succprec` and `\nsuccprec` for `\compat` and `\incompat` pass the option `altcompat`

<code>\str{1,0,1}</code>	$\langle 1, 0, 1 \rangle$	Strings/Codes for strings
<code>\code{5,8,13}</code>	$\langle\langle 5, 8, 13 \rangle\rangle$	
<code>\EmptyStr</code>	$\langle \rangle$	Empty string
<code>\estr</code>	$\langle \rangle$	
<code>\godelnum{\phi}</code>		Godel Code/Corner Quotes
<code>\cornerquote{\phi}</code>		
<code>\decode{\sigma}{3}</code>	$(\sigma)_3$	Alternate notation for $\sigma(3)$
<code>\sigma\concat\tau</code>	$\sigma \hat{\wedge} \tau$	Concatenation
<code>\sigma\concat[0]</code>	$\sigma \hat{\wedge} \langle 0 \rangle$	
<code>\strpred{\sigma}</code>	σ^-	The immediate predecessor of σ
<code>\lh{\sigma}</code>	$ \sigma $	Length of σ
<code>\sigma \incompat \tau</code>	$\sigma \perp \tau$	Incompatible strings
<code>\sigma \compat \tau</code>	$\sigma \not\perp \tau$	Compatible strings
<code>\sigma \nsuccprec \tau</code>	$\sigma \not\asymp \tau$	Alternate incompatible strings
<code>\sigma \succprec \tau</code>	$\sigma \asymp \tau$	Alternate compatible strings
<code>\pair{x}{y}</code>	$\langle x, y \rangle$	Code for the pair (x, y)
<code>\setcol{X}{n}</code>	$X^{[n]}$	$\{y \mid \langle n, y \rangle \in X\}$
<code>\setcol{X}{\leq n}</code>	$X^{[\leq n]}$	$\{\langle x, y \rangle \mid \langle x, y \rangle \in X \wedge x \leq n\}$

3.12. **Subfunctions.** To disable these commands pass the option `nosubfuns`.

$f \backslash\text{subfun } g$	$ f \prec g $	Varieties of the function extension relation
$f \backslash\text{supfun } g$	$ f \succ g $	
$f \backslash\text{nsubfun } g$	$ f \not\prec g $	
$f \backslash\text{nsupfun } g$	$ f \not\succ g $	
$f \backslash\text{subfuneq } g$	$ f \preceq g $	
$f \backslash\text{subfunneq } g$	$ f \preceq g $	
$f \backslash\text{supfuneq } g$	$ f \succeq g $	
$f \backslash\text{supfunneq } g$	$ f \succeq g $	
$f \backslash\text{nsubfuneq } g$	$ f \not\preceq g $	
$f \backslash\text{nsupfuneq } g$	$ f \not\succeq g $	

3.13. **Trees.** To disable these commands pass the option `notrees`.

$\backslash\text{CBderiv}\{T\}$	$ T^{\langle 1\rangle} $	Cantor-Bendixson Derivative
$\backslash\text{CBderiv}[\backslash\alpha]\{T\}$	$ T^{\langle\alpha\rangle} $	
$\backslash\text{pruneTree}\{T\}$	$ T^{\langle\infty\rangle} $	$\{\sigma \in T \mid (\exists g)(g \in [T] \wedge \sigma \subset g)\}$
$\backslash\text{hgt}\{T\}$	$ \ T\ $	Tree Height
$\backslash\text{TreeMod}\{T\}\{\backslash\sigma\}$	$ T / \sigma $	$\{\tau \mid \sigma \hat{\cdot} \tau \in T\}$
$\backslash\sigma \backslash\text{TreeMul } T$	$ \sigma * T $	$\{\sigma \hat{\cdot} \tau \mid \tau \in T\}$

3.14. **Set Relations.** To disable these commands pass the option `nosetrels`. Note that many of these commands are extensions of existing commands.

$X \setminus \text{subset}* Y$	$X \subset^* Y$	All but finitely much of X is in Y
$X \setminus \text{subseteq}* Y$	$X \subseteq^* Y$	
$X \setminus \text{superset}* Y$	$X \supset^* Y$	All but finitely much of Y is in X
$X \setminus \text{supseteq}* Y$	$X \supseteq^* Y$	
$X \setminus \text{eq} Y$	$X = Y$	Macro for =
$X \setminus \text{eq}* Y$	$X =^* Y$	Equal mod finite
$X \setminus \text{eqae} Y$		
$X \setminus \text{infssubset} Y$	$X \subset_\infty Y$	$X \subset Y \wedge Y \setminus X = \omega$
$X \setminus \text{infssubset}* Y$	$X \subset_\infty^* Y$	$X \subset^* Y \wedge Y \setminus X = \omega$
$X \setminus \text{infsupset} Y$	$X \supset_\infty Y$	$Y \subset X \wedge X \setminus Y = \omega$
$X \setminus \text{infsupset}* Y$	$X \supset_\infty^* Y$	$Y \subset^* X \wedge X \setminus Y = \omega$
$X \setminus \text{majsubset} Y$	$X \subset_m Y$	X is a major subset of Y
$X \setminus \text{majsupset} Y$	$X \supset_m Y$	Y is a major subset of X

3.15. Ordinal Notations. To disable these commands pass the option `noordinalnotations`. Note the name for addition is `\Oadd` rather than `\Oplus` to avoid a collision with existing commands.

<code>\wck</code>	ω_1^{CK}	First non-computable ordinal
<code>\Oabs{\alpha}</code> <code>\Ohgt{\alpha}</code>	$\ \alpha\ _{\mathcal{O}}$	The height of the notation or well-ordering α (i.e. ordinal) Alternative command
<code>\kleene0</code> <code>\kleene0-</code> <code>\kleene0+</code> <code>\kleene01</code> <code>\kleene0*</code> <code>\kleene0(X)</code> <code>\kleene0[\alpha]</code> <code>\kleene01(X)[\alpha]</code>	\mathcal{O} $\overline{\mathcal{O}}$ ${}^+\mathcal{O}$ \mathcal{O}_1 \mathcal{O}^* \mathcal{O}^X \mathcal{O}_{α} $\mathcal{O}_1^X[\alpha]$	Set of ordinal notations Set of limit notations Set of successor notations Canonical unique set of ordinal notations Set of apparent ordinal notations, i.e., includes non-standard Relativized ordinal notations Ordinal notations for ordinals $< \alpha $ Multiple options work together
<code>\alpha \Oless \beta</code> <code>\alpha \Oleq \beta</code>	$\alpha <_{\mathcal{O}} \beta$ $\alpha \leq_{\mathcal{O}} \beta$	less than on the ordering on notations
<code>\alpha \Ogtr \beta</code> <code>\alpha \Ogeq \beta</code> <code>\alpha \Onless \beta</code> <code>\alpha \Onleq \beta</code>	$\alpha >_{\mathcal{O}} \beta$ $\alpha \geq_{\mathcal{O}} \beta$ $\alpha \not<_{\mathcal{O}} \beta$ $\alpha \not\leq_{\mathcal{O}} \beta$	less than on the ordering on notations
<code>\alpha \Ongtr \beta</code> <code>\alpha \Ongeq \beta</code>	$\alpha \not>_{\mathcal{O}} \beta$ $\alpha \not\geq_{\mathcal{O}} \beta$	
<code>\alpha \Oadd \beta</code>	$\alpha +_{\mathcal{O}} \beta$	Effective addition of notations
<code>\alpha \Omul \beta</code>	$\alpha \cdot_{\mathcal{O}} \beta$	Effective multiplication of notations
<code>\Olim{\lambda}{n}</code>	$\vec{\lambda}_n$	The n -th element in effective limit defining notation λ
<code>\Opred{\alpha}</code>	α^-	Predecessor of α if defined
<code>\Ofunc{\gamma}{m}</code>	$\{\gamma\}^{\mathcal{O}}(m)$	The m -th element in the effectively given limit defining t

3.16. **Forcing.** To disable these commands pass the option `noforcing`.

<code>\sigma \forces \phi</code>	$\sigma \Vdash \phi$	σ forces ϕ
<code>\sigma \forces(X) \phi</code>	$\sigma \Vdash_T^X \phi$	ϕ is formula relative to X
<code>\sigma \forces(X)[T] \phi</code>	$\sigma \Vdash_T^X \phi$	Local forcing on T relative to X
<code>\sigma \forces* \phi</code>	$\sigma \Vdash^* \phi$	Strong forcing
<code>\sigma \wforces \phi</code>	$\sigma \Vdash^{-w} \phi$	weak forcing (takes optional paren and bracket arguments)

3.17. **Syntax.** To disable these commands pass the option `nosyntax`.

All syntax classes can be relativized with an optional argument in square brackets even when not listed below. Only the Δ formula classes are listed below since the syntax is identical for Σ and Π . Adding a star after the command produces the boldface version. Do to the common usage of the

zero and one versions of the formulas an abbreviation is provided unless the option `noshortsyntax` is passed.

\DeltaN{2}	Δ_2	
\DeltaN(X){2}	$\Delta_2(X)$	
\DeltaN[X]{2}	Δ_2^X	
\DeltaN[X]{2}	Δ_2^X	boldface
\DeltaZeroN{2}	Δ_2^0	
\DeltaZeroN(X){2}	$\Delta_2^0(X)$	
\DeltaZeroN[X]{2}	$\Delta_2^{0,X}$	
\DeltaZeroN[X]{2}	$\Delta_2^{0,X}$	boldface
\deltazn(X){2}	$\Delta_2^0(X)$	Abbreviated form
\DeltaOneN{2}	Δ_2^1	
\DeltaOneN(X){2}	$\Delta_2^1(X)$	
\DeltaOneN[X]{2}	$\Delta_2^{1,X}$	
\DeltaOneN[X]{2}	$\Delta_2^{1,X}$	boldface
\deltain(X){2}	$\Delta_2^1(X)$	Abbreviated form
\logic{\omega_1}{\omega}	$\mathcal{L}_{\omega_1, \omega}$	Indicates the kind of infinitary logic

3.18. Proof Cases. The pfcases environment provides a numbered, referenceable division of a proof segment into cases. Pass the option `nopfcases` to disable loading of this feature. Note these features are not available if you are using the package in a beamer document (not likely to be an issue).

To see how these commands work consider the following code.

```
\begin{proof}
\begin{pfcases}
\case[(x = y)]\label{case:first} %
    Lorem ipsum dolor sit amet, consectetur adipiscing elit. In et enim eget nisl luctus
    Vestibulum semper eget velit ut lobortis. In vel finibus est. Nullam tellus dolor, p

\case[(x = z \land z > q \land z < r \land x + z = r)]\label{case:second} %
    Quisque consectetur, felis non congue dictum, mauris mi suscipit sem, vel laoreet ju

\begin{pfcases}
\case[(x=2)]\label{case:second:sub1} %
    ipsum dolor sit amet, consectetur adipiscing elit. In et enim eget nisl luctus venenatis
\case[(x = 3)]\label{case:second:sub2} %
    consectetur adipiscing elit. In et enim eget nisl luctus venenatis. Pellentesque sed
\end{pfcases}

\end{pfcases}
\end{proof}
We can now reference the case number \ref{case:second} and cleverref \cref{case:second}
```

This produces the following output.

Proof. CASE 1 $x = y$: Lorem ipsum dolor sit amet, consectetur adipiscing elit. In et enim eget nisl luctus venenatis. Pellentesque sed erat sodales, tincidunt quam non, eleifend risus. Fusce aliquam dignissim pharetra. Integer id dui ac libero tincidunt consectetur. Sed laoreet nunc nec semper laoreet.

Vestibulum semper eget velit ut lobortis. In vel finibus est. Nullam tellus dolor, pellentesque sed orci sed, ornare pretium diam. Nam vel tincidunt tellus. Nulla at mi nisl.

CASE 2 $x = z \wedge z > q \wedge z < r \wedge x + z = r$: Quisque consectetur, felis non congue dictum, mauris mi suscipit sem, vel laoreet justo ipsum in tellus. Suspendisse blandit malesuada velit faucibus pulvinar.

CASE 2a $x = 2$: ipsum dolor sit amet, consectetur adipiscing elit. In et enim eget nisl luctus venenatis. Pellentesque sed erat sodales, tincidunt quam non, eleifend risus. Fusce aliquam dignissim pharetra. Integer id dui ac libero tincidunt consectetur. Sed laoreet nunc nec semper laoreet.

CASE 2b $x = 3$: consectetur adipiscing elit. In et enim eget nisl luctus venenatis. Pellentesque sed erat sodales, tincidunt quam non, eleifend

□

We may reference the case number 2 and cleeref `case 2` as well as case 2a and cleeref `case 2b`.

To skip numbering and instead reference with the argument to `\case` use `pfcases*`. For instance, consider the following code.

```
\begin{proof}
\begin{pfcases*}
\case[\((x = y)\)]\label{case*:first} Lorem ipsum dolor sit amet, consectetur
adipiscing elit. In et enim eget nisl luctus venenatis. Pellentesque sed erat
sodales, tincidunt quam non, eleifend risus. Fusce aliquam dignissim pharetra.
Integer id dui ac libero tincidunt consectetur. Sed laoreet nunc nec semper
laoreet.
```

Vestibulum semper eget velit ut lobortis. In vel finibus est. Nullam tellus dolor, pellentesque sed orci sed, ornare pretium diam. Nam vel tincidunt tellus. Nulla at mi nisl.

```
\case[\((x = z \land z > q \land z < r \land x + z = r)\)] \label{case*:second}
Quisque consectetur, felis non congue dictum, mauris mi suscipit sem, vel
laoreet justo ipsum in tellus. Suspendisse blandit malesuada velit faucibus
pulvinar.
```

```
\begin{pfcases*}
\case[\(( x=2 \))] \label{case*:second:sub1} Lorem ipsum dolor sit amet,
\consectetur adipiscing elit. In et enim eget nisl luctus venenatis.
\Pellentesque sed erat sodales, tincidunt quam non, eleifend risus. Fusce
\aliquam dignissim pharetra. Integer id dui ac libero tincidunt consectetur. Sed
\laoreet nunc nec semper laoreet.

\case[\(( x = 3 \))] \label{case*:second:sub2} consectetur adipiscing elit. In et
\enim eget nisl luctus venenatis. Pellentesque sed erat sodales, tincidunt quam
\non, eleifend
\end{pfcases*}
\end{pfcases*}
\end{proof}
```

Again we can ref case `\ref{case*:second}` and cleverref that `\cref{case*:second}`. Also

Proof. CASE $x = y$: Lorem ipsum dolor sit amet, consectetur adipiscing elit. In et enim eget nisl luctus venenatis. Pellentesque sed erat sodales, tincidunt quam non, eleifend risus. Fusce aliquam dignissim pharetra. Integer id dui ac libero tincidunt consectetur. Sed laoreet nunc nec semper laoreet.

Vestibulum semper eget velit ut lobortis. In vel finibus est. Nullam tellus dolor, pellentesque sed orci sed, ornare pretium diam. Nam vel tincidunt tellus. Nulla at mi nisl.

CASE $x = z \wedge z > q \wedge z < r \wedge x + z = r$: Quisque consectetur, felis non congue dictum, mauris mi suscipit sem, vel laoreet justo ipsum in tellus. Suspendisse blandit malesuada velit faucibus pulvinar.

CASE $x = 2$: Lorem ipsum dolor sit amet, consectetur adipiscing elit. In et enim eget nisl luctus venenatis. Pellentesque sed erat sodales, tincidunt quam non, eleifend risus. Fusce aliquam dignissim pharetra. Integer id dui ac libero tincidunt consectetur. Sed laoreet nunc nec semper laoreet.

CASE $x = 3$: consectetur adipiscing elit. In et enim eget nisl luctus venenatis. Pellentesque sed erat sodales, tincidunt quam non, eleifend

□

Again we can ref case $x = z \wedge z > q \wedge z < r \wedge x + z = r$ and cleverref that case $x = z \wedge z > q \wedge z < r \wedge x + z = r$. Also case $x = 2$ and cleverref subcase $x = 3$.

If the choice of cleverref labels aren't to your taste please let me know and I will consider changing them. Also, note that by passing the options

`pfcasefont=textit` one can change the font used to typeset Case to italics (or whatever other font command you choose).

3.19. Steps. To enable the steps environment you *must* pass the option `steps` when loading the package. This enables use of the steps environment to typeset presentation of procedures. The command `\begin{steps}` starts a list environment with an optional argument which is passed along unchanged as the optional argument to the underlying enumitem based list. Inside the steps environment the command `\step[steptitle]` prints a numbered step with steptitle displayed in bold. An example of the use of the steps environment is provided below.

```
\begin{steps}
  \step If \(\ x=5 \) fails to hold end the stage without acting. Otherwise the mod
        le acts by executing the subsequent steps.

  \step If there is \( k < m \) with \( s_{\{k\}} - 1 \approx_i s - 1 \) perform the
        following steps
    \begin{steps}
      \step Choose \( a \in \setcol{A}{1} \) large.
      \step Set \( c = c_k, b = b_k, \hat{s}_0 = s_{\{k\}} - 1, \hat{s}_1 = s - 1 \)
      \step Enumerate \( b \) into \( \setcol{A}{2} \) and set \( R_{j,e}(s) = 2 \)
    \end{steps}
  \step If there is no such \( k \) we instead enumerate \( c_m \) into \( \setcol{A}{3} \)

\end{steps}
```

This yields the following output:

- Step 1 If $x = 5$ fails to hold end the stage without acting. Otherwise the module acts by executing the subsequent steps.
- Step 2 If there is $k < m$ with $s_k - 1 \approx_i s - 1$ perform the following steps and end the stage.
 - Step 2a Choose $a \notin A^{[1]}$ large.
 - Step 2b Set $c = c_k, b = b_k, \hat{s}_0 = s_k - 1, \hat{s}_1 = s - 1$.
 - Step 2c Enumerate b into $A^{[2]}$ and set $R_{j,e}(s) = 2$
- Step 3 If there is no such k we instead enumerate c_m into $A^{[3]}$ and execute the procedure for expansionary stages.

4. FONT NOTES

The package is designed to work with both XITS fonts using `unicode-math` under `lualatex` and `xelatex` as well as standard fonts under `pdflatex`. The package will assume that XITS or a font with similar features is loaded if the `unicode-math` package is loaded. To properly represent symbols the package needs access to different `mathcal` and `mathscr` fonts. By default, if `unicode-math` isn't loaded the package will load `mathrsfs`. To disable this behavior

pass the option `norsfs`. Furthermore, it also needs access to a blackboard bold that works for lowercase symbols. This isn't an issue using XITS but if `unicode-math` isn't loaded the package will load the `mathbbm` package to define certain symbols. This behavior can be overridden by passing the option `nobbbm` and the package will do the best it can.

5. RELEASE NOTES

- 4.5 2025/04/19 - Added versioning interface. Finally fixed references to cases. At least largely. Fixed `\supfunneq` to face the right direction. **Breaking** change to `\kleene0` in arguments. Added `\leftofneq`, and `\rightofneq` improved `\succprec`, `\precsucc` and made them the default compatibility symbols, removed old not hack for `unicode-math`. Supplemented `\gg` `\ll` with `\ggneq` `\ggeq` and like. Added relations `\KBless` `\KBgtr` and so on. Improved command `\wck` to take a relativization argument in parens as well as brackets for greater uniformity. Added generalized low/high/intermediate degree class symbols `\GHn` `\GLn` `\GIn` and improved interaction between `cleverref` and the `steps` command. Added an optional argument to the `\hgt` command to specify the ordering. Improved spacing for `\deltain{1}`, fixed `\wck[g]`. Added operator `\id` Changed the size of the meet and join operators to distinguish them from and and or. Improved `recfnl` to work without an oracle argument.
- 4.0 Stripped out non-working compatibility code and removed previously depreciated features. Removed `mref` helper. Removed the `ball` command. Removed undocumented hyphenation. Removed the recursive/computably terminology commands. Removed lots of unnecessary syntax commands and reworked the code to be simpler. Added option not to load `rsfs`. Added the commands `\succprec`, `\precsucc`, `\csuccprec`, `\cprecsucc` for stacked succ/prec symbols and added the option `altcompat` to use these instead of the standard `mid` and `not mid` compatibility symbols. Added the `\Searrow` symbol from `MnSymbol` and changed option from `nodelim` to `nosymb`. Changed commands for `\StrcR` and `\StrcD` to be `\strcR` and `\strcD` for consistency and added `\strcRa` and `\strcDa` as synonyms for `\Adegrees` and `\AREAdegrees`. Added `\Adegrees` and `\AREAdegrees` and the relations for arithmetic degrees. Merged the degree symbols into the `degrees` option and depreciated some alternate spellings. Added `\TreeMul`, `\TreeMod`, `\TreeExt`, `\wforces`, `\HYP`, depreciated the computable classes of sentences and simplified the standard ones. Fixed `\nconv` to be the symbol from `MnSymbol` if the `nosymb` option isn't passed, fixed `\concat` to not be so far above the line. Adjusted spacing for `\compat`, added abbreviations. Complete renaming and of the commands for ordinal notations and extra options to indicate limit, successor and unique sets of notations. Added

\Ofunc as the effective limit for a notation. Fixed errors in the pf-cases environment and eliminated some old compatibility code that wasn't being used by anyone. Added \maps helper for normal math stuff. Fixed BeamerRequirements. Added the \bpfuncs command and \cbstrs. Removed dependency on mathtools for compatibility with asl.cls

Adjusted a number of other command names/conventions and deleted redundant commands. Large scale simplification and deduplication. Made substantial changes to documentation to reflect this.

3.8.2 Removed option to put the set at the end of an \REset operation to avoid capturing later parenthesized arguments, e.g. \REset{i}(A) no longer works to avoid confusion with \REset{i}(x). Fixed failed pdf doc update.

3.8.1 Fixed issues displaying the prime for jump operations.

3.8 Adjusted \Tdeg to be more beamer friendly and fixed it not to dumbly underline 0^n . Fixed BeamerRequirements to work with differing values of \abovedisplayskip. Removed a few typos in docs for the requirements assistance. Added BeamerRequire and BeamerRequire* that put the requirements in a block and offer overlay specifications.

3.7 Fixed cases environment (both prettier and no problem with creating newline). Major re-factor to fix all options. Fixed bug with \set display. Added \st command inside the \set command to deprecate second argument. Added \finSsets (alt \ssetsOfsize), \finsets and optional argument to \powset. Changed \REAop so the hat is on the starred version as intended. Added the steps (experimental) environment which requires an option to enable and fixed some problems with existing options. Reimplemented \REset to use xparse to avoid some errors in unusual contexts. Fixed the display of \tpath. Deprecated \iREAop and \oneREAop. Fixed \Join.

3.6 Fixed \REA[n] so that dash is shorter. Added BeamerRequirements to add a block for requirements in beamer and fixed the requirements environment for beamer. Fixed \req* error. Improved syntax for \recfnl so it can accept a parenthesis delimited argument as the oracle. Improved \setcol to allow it to be used in a nested fashion without typesetting bugs. Changed the \code and \pair commands to use only a single angle bracket.

3.5 Added \Hop and misc code cleanup.

3.4 Eliminated dependence on undertilde which is missing from texlive

3.3.1 Fixed typo causing error under pdflatex.

3.3 - Fixed/added tweak to overline so it looks correct. Also added real symbols so that `\subfunneq` and `\supfunneq` can be defined appropriately. Added `\floor` and `\ceil`. Note these aren't yet shown off in package doc. Fixed incorrect use of tiny in math mode.

3.2 - Removed `\reaop`, `\alphaREAop`, `\aREAop` in favor of using the single form `\REAop`. Removed `\functo`, `\map` and `funcmap`, `\hgt0` as useless synonyms and removed `\Kleene0Below` and `Kleene0Less` as beyond what the package should define. Added package option `compat31` to ensure package compatibility with version 3.1. An optional parentheses delimited argument specifying the base has been added to `\REAop`. Both `\REAop` and the pair `\REA/\CEA` have been updated to ignore order of optional arguments. The square brackets used to delimit the argument to the `use` command are now auto-sized. Added `\pmapsto`, `\pmapsfrom`, `\kleeneZero`, `\kleeneNum`, `\entersat`. Also Misc typesetting fixes.

3.1 02/26/2019 - Fixed `\wck` to be ω_1^{CK} , i.e., have capitalized roman CK.

3.01 02/17/2019 - Fixed `\RE` `\CE` `\Re` and `\Ce` for the various capitalized versions. Fixed weird bug with `\recfnl` no longer working based on let. Removed `\interior` and `\closure` as not really appropriate commands for the package and having bugs. Also fixed package to have correct version.

3.0 02/16/2019 - Added requirements environment for multiple requirements. Changed the `\req` and `\require` commands to take their optional argument after the first mandatory arguments as well as before. Added the commands `\module` and `\modof` and `\xor`. Improved the corner quotes. Added `\leftofeq`, `\rightof`, `\rightofeq`. Added `\RE`, `\CE`, `\Ce`, `\Re` and `\Tincompat`, `\Tincomp`, `\Tcompat`. Changed the way strings are symbolized and coded. Fixed suffix commands to work with unicode-math. Also added `\require*` inside `\requirements`. Added `\nleftofeq`, `\nrightof`, `\nrightofeq`, `\nleftof`. The commands `\ancestor`, `\descendant` etc... `\reqof`, `\Astages` and `\Vstages` now require the option `suppPriorityTrees` be passed to the class to use and should be viewed as deprecated. Fixed the options system so different symbols can be correctly passed to the class. Changed the way `\recf` works to comply with the usual syntax.

2.4.3 11/29/2018 - Rendered compatible with beamer by removing enumitem requirement if beamer is loaded.

2.4.2 11/29/2018 - Fixed horrible bugs introduced in last version and fixed many symbols to work even in pdflatex mode. Also have everything compiling again.

- 2.4.1 2/14/2018 - Moved to using xparsse to define the case macros and several other macros to allow nested brackets for optional arguments. Added the recf command and cleaned up some option processing. Also worked around the mathtools/unicode-math font bug described [here](#)
- 2.4 1/17/2018 - Added priority tree helpers. Should be more robust with respect to existing definitions of common commands.
- 2.3 12/31/2017 - Added proof cases helper. Also fixed the issue with \nctequiv in X_ELaT_EX
- 2.2 11/14/2017 - Fixed \Tdeg so it works different on symbols and vars and added \Tdegof and \Tvarof. Added \subfunneq and \supfunneq.
- 2.1 10/05/2017 - Fixed way packages are required so rec-thy can be loaded in a flexible order. Also fixed one or two bugs.
- 2.0 09/26/2017 - Added support for introducing requirements, the sub-function relation and probably other undocumented features
- 1.3 06/20/2012 - Added abbreviations for computable infinitary formulas and made a few minor fixes.
- 1.2 01/01/2011 - Fixed awful option processing bug preventing most options from being recognized and added mrref option.
- 1.0 10/15/2010 - Initial public release